



H.S. WHITE CORPORATION

Marine and Industrial Specialties

1350 S. Dixie Highway East • Pompano Beach, FL 33060
Pompano (954) 785-6760 Miami (305) 940-2700 W.P.B. (561) 832-4144
Fax (954) 785-8247 Website: www.HSWHITE.com

DX BAF nbr

If you need to seal against steam, we recommend Style BAF. It is a premium grade compressed sheet, manufactured with high temperature synthetic and graphite fibers and an NBR binder.

Recommended for use in sealing against water, steam, fuel, lubricant alkalis, and weak acids, in service conditions up to 850°F.

- Synthetic Fiber and Graphite
- NBR Binder
- Available 60" x 60" and 60" x 120"
- Premium Quality Steam Sheet

Physical Properties

| | |
|---|----------|
| Color | Black |
| Density (lb/cubic ft) | 105 |
| Maximum Service Temperature | 850°F |
| Maximum Service Pressure | 1450 psi |
| Compressibility @ 5000 psi (%) | 7-17% |
| Recovery Minimum (%) | 60% |
| Creep Relaxation ASTM F38B (max%) | 19% |
| Tensile Strength (ASTM F146 (against the grain) | 2390 |
| Thickness Increase (max%) ASTM F146 (ASTM Oil #3) | 0-5% |
| Weight Increase (max%) ASTM F146 (ASTM Oil Fuel B) | 15% |
| Thickness Increase (max%) ASTM F146 (ASTM Oil Fuel B) | 0-5% |

1/32"-1/16" 3/32" 1/8"