



H.S. White Corporation

Your Marine & Industrial Specialists

1350 South Dixie Highway East | Pompano Beach, FL 33060
800-327-8575 | sales@hswhite.com | www.HSWhite.com
Pompano Beach: 954-785-6760 | Houston: 713-589-8591

RED RUBBER SHEET-TYPE 95

Styrene Butadiene Rubber Sheet (Red Rubber) is a low-cost flange gasket material recommended for low temperature applications such as washers and gaskets for the heating and plumbing trades. Red Rubber is a non-oil resistant compound that resists flow under compression. It offers moderate to good performance against low pressure. Good aging and abrasion resistance and easily conforms to uneven flange faces.

The low resistance to oils makes Red Rubber better suited for general gasket applications in no-petroleum-based systems.

DURO: 75
ELONGATION: 200%
COLOR: Red-Brown

TENSILE: 400 psi
TEMP: to 180°F

Features: Plate Finish

GAUGE (inch)	WIDTH (inch)	LENGTH (ft/roll)	WEIGHT approx. lbs/sq.yd
1/32"	36	50	2.50
1/16"	36 or 48	50	5.75
3/32"	36	50	7.75
1/8"	36 or 48	50	11.50
3/16"	36 or 48	50	17.25
1/4"	36 or 48	25	23.00